



Algorithms: Design
and Analysis, Part II

Advanced Union-Find

Path Compression: The
Hopcroft-Ullman Analysis

Hopcroft-Ullman Theorem

Theorem: [Hopcroft - Ullman 73] with Union by Rank and path compression, m Union + Find operations take $O(m \log^* n)$ time, where

$\log^* n$ = the number of times you need to apply log to n before the result is ≤ 1

[will focus on interesting case where $m = \Omega(n)$]

Measuring Progress

Intuition: installing shortcuts should significantly speed up subsequent FINDS + UNIONs.


Question: how to track this progress and quantify the benefit?

Idea: consider a non-root object x . → recall: $\text{rank}[x]$ frozen forevermore

Progress measure: $\text{rank}[\text{parent}(x)] - \underline{\text{rank}[x]}$.

Path compression increases this progress measure

If x has old parent p , new parent $p' \neq p$, then $\text{rank}[p'] > \text{rank}[p]$.



Proof Setup

Rank blocks: $\{0\}, \{1, 2, 3, 4\}, \{5, \dots, 2^4\}, \{17, 18, \dots, 2^{16}\}, \{65537, \dots, 2^{65536}\}, \dots, \{\dots, n\}.$

65536

2^{16}

Note: There are $O(\log^* n)$ different rank blocks.

Semantics: traversal $x \rightarrow \text{parent}(x)$ is "fast progress" $\Leftrightarrow \text{rank}[\text{parent}(x)]$ in larger block than $\text{rank}[x]$

Definition: At a given point in time, call object x good if

- ① x or x 's parent is a root OR
- ② $\text{rank}[\text{parent}(x)]$ in larger block than $\text{rank}(x)$

x is
bad
otherwise

Proof of Hopcroft-Ullman

Point: every FWD visits only $O(\log^* n)$ good nodes
 $\{2 + \# \text{ of rank blocks} = O(\log n)\}$.

visits to good objects

Upshot: total work done during m operations =
need to bound globally by separate argument

$O(m \log^* n)$

+ total # of visits to bad nodes

Consider: a rank block $\{k+1, k+2, \dots, 2^k\}$.

Note: when a bad node x is visited , its parent is changed to one with strictly larger rank. \Rightarrow can only happen 2^k times before x becomes good (forevermore)

Proof of Hopcroft-Ullman II

Total work: $\Theta(m \log^* n) + O(\# \text{visits to bad nodes})$

Consider: a rank block $\{k+1, k+2, \dots, 2^k\}$.

$\leq n$ for each
of $O(\log^* n)$
rank blocks

Last slide: for each object x with final rank in this block,
 $\# \text{visits to } x \text{ while } x \text{ is bad} \leq 2^k$.

Rank lemma: total number of objects x with final rank in this
rank block is $\sum_{i=k+1}^{2^k} n/2^i \leq n/2^k$

$\leq n$ visits to bad
objects in this
rank block

Recall: only $O(\log^* n)$ rank blocks.

Total work: $O(mn \log^* n)$.

QED!