

# Fundamentals of Electrical Engineering

## The Frequency Domain

- Signal power in the frequency domain
- Building signals in the frequency domain
- Filtering periodic signals

# Parseval's Theorem

$$s(t) = \sum_{k=-\infty}^{\infty} c_k e^{j \frac{2\pi k t}{T}} \quad c_k = \frac{1}{T} \int_0^T s(t) e^{-j \frac{2\pi k t}{T}} dt$$

Power in time-domain equals power in the frequency domain

$$\text{power}[s] \equiv \frac{1}{T} \int_0^T s^2(t) dt$$

$$\boxed{\frac{1}{T} \int_0^T s^2(t) dt = \sum_{k=-\infty}^{\infty} |c_k|^2}$$

# Approximation of Signals



$$s(t) = \sum_{k=-\infty}^{\infty} c_k e^{j \frac{2\pi k t}{T}}$$

$$s_K(t) = \sum_{k=-K}^K c_k e^{j \frac{2\pi k t}{T}}$$

$$\epsilon_K(t) = s(t) - s_K(t) = \sum_{k=-\infty}^{-K-1} c_k e^{j \frac{2\pi k t}{T}} + \sum_{k=K+1}^{\infty} c_k e^{j \frac{2\pi k t}{T}}$$

$$\text{rms}(\epsilon_K) = \sqrt{2 \sum_{k=K+1}^{\infty} |c_k|^2}$$


# Approximation of Square Wave



RICE

# Harmonic Distortion

How close to a sinusoid is a periodic waveform?



$$c_1 = \frac{2}{j\pi}$$


$$\text{THD} = \frac{\frac{2}{\text{power}(s(t) - c_0)} \sum_{k=2}^{\infty} |c_k|^2}{\frac{2}{\text{power}(s(t) - c_0)} \sum_{k=1}^{\infty} |c_k|^2} = \frac{\frac{1 - 2 \left(\frac{2}{\pi}\right)^2}{1}}{1} = 0.1894$$

Note:  $c_0 = \frac{1}{T} \int_0^T s(t) dt$  = average value of  $s(t)$


# A Glimpse of Digital Communication

Digital communication:	$“0” \rightarrow 0$	$0 \leq t < T$
(one bit at a time)	$“1” \rightarrow \sin 2\pi f_c t$	
(two bits at a time)	$“00” \rightarrow 0 + 0$	
	$“01” \rightarrow 0 + \sin 2\pi f_2 t$	$0 \leq t < T$
	$“10” \rightarrow \sin 2\pi f_1 t + 0$	
	$“11” \rightarrow \sin 2\pi f_1 t + \sin 2\pi f_2 t$	

# Encoding Information in the Frequency Domain



# Linear, Time-Invariant Filters




- If  $x(t) = e^{j2\pi ft}$ ,  $y(t) = H(f)e^{j2\pi ft}$
- If  $x(t) = e^{j\frac{2\pi kt}{T}}$ ,  $y(t) = H\left(\frac{k}{T}\right)e^{j\frac{2\pi kt}{T}}$
- If  $x(t) = c_{k_1}e^{j\frac{2\pi k_1 t}{T}} + c_{k_2}e^{j\frac{2\pi k_2 t}{T}}$   
$$y(t) = H\left(\frac{k_1}{T}\right)c_{k_1}e^{j\frac{2\pi k_1 t}{T}} + H\left(\frac{k_2}{T}\right)c_{k_2}e^{j\frac{2\pi k_2 t}{T}}$$
- If  $x(t) = \sum_{k=-\infty}^{\infty} c_k e^{j\frac{2\pi k t}{T}}$ ,  $y(t) = \sum_{k=-\infty}^{\infty} H\left(\frac{k}{T}\right) c_k e^{j\frac{2\pi k t}{T}}$





RICE

# Lowpass Filtering



$$H(f) = \frac{1}{1 + j2\pi RC f}$$



# Signals in Time and Frequency

$$s(t) = \sum_{k=-\infty}^{\infty} c_k e^{j \frac{2\pi k t}{T}} \quad c_k = \frac{1}{T} \int_0^T s(t) e^{-j \frac{2\pi k t}{T}} dt$$
$$s(t) \longleftrightarrow c_k$$

- Signals can be defined in either the time domain or the frequency domain
- Can study a signal's structure in either domain
- For linear, time-invariant systems, we can determine their outputs for periodic inputs